

# BRI CARD (PCI/PCIe)



Certified by



Also works with



Each of the 4 ports can be independently  
configured for TE or NT mode

Line Echo Cancellation

Fully PCI 2.2/PCIe compliant

Certified by ELASTIX™, our BRI card uses the same Cologne™ chipset as all the other manufacturers, yet costs less.

It supports the EURO and US flavor ISDN (2B+D) circuits. Easy jumper settings allows for either ISDN lines or phones to be connected to the cards 2 or 4 ports.

## Features

- 64 ms tail line echo cancellation powered by Octasic™
- 2 or 4 BRI ports interface
- Up to 8 simultaneous voice calls over 4 ISDN BRI lines
- Independently configure each port for TE or NT
- Conference bridge
- Onboard power feeding
- Point-to-point (TE/NT) and point-to-multipoint (TE/NT) Euro ISDN protocol stack
- Fully PCI 2.2/PCIe compliant
- Compatible with 5V and 3.3V PCI busses automatically detectable
- DTMF detection on all B-channels

## Minimum Hardware Requirement

- Dual core processor
- 1 GB RAM
- Available PCI/PCIe slot

Operation temperature: 0°C to 50°C  
Storage Temperature: -40°C to 125°C  
Dimensions: 15.4cm x 8.7cm x 1.8cm  
Weight: 102g\*

## Warranty Info

**5 Years** Hardware warranty.

## Product Models

**aCB2** - 2 PORT BRI PCI card

**aCB2e** - 2 PORT BRI PCIe card

**aCB2eL** - 2 PORT BRI PCIe card + LEC

**aCB2L** - 2 PORT BRI PCI Card + LEC

**aCB4** - 4 PORT BRI PCI card

**aCB4e** - 4 PORT BRI PCIe card

**aCB4eL** - 4 PORT BRI PCIe card + LEC

**aCB4L** - 4 PORT BRI PCI card + LEC

allo.com

9 Sarantaporou Str.  
155 61 Hologos, Greece  
T: +30 210 2116501, F: +30 210 6543652  
sales@partnet.gr, www.partnet.gr