

Product Introduction

This smart socket uses the standard ZigBee protocol for seamlessly integration with smart home gateways, enabling collaboration with various devices to create a personalized smart home ecosystem. With remote control and timer features, it offers efficient energy management for convenient smart living.

Features

- Timer function
- Broad-range voltage design, encompassing a wide spectrum of applications.
- Standard European specification
- Low power consumption design with safety protection features
- Supports Belahome APP and HyPanel control



Specification

- Product Model: SM-PW735-EZ /SM-PW732-E
- Input Voltage: 110 ~ 240VAC, 50/60Hz
- Maximum Current: 16A
- Indicator Light: Blue light flashing quickly indicates standby for network pairing, red indicates power on
- Communication Mode: ZigBee 3.0
- Load Limit: 2200W
- Housing Material: PC+ABS (fireproof)
- Operating Temperature: -30 ~ 70°C
- Operating Humidity: 0 ~ 95%RH(non-condensing)
- Product Dimensions: 50×50×83.5mm

Networking method

1. Insert the device into the socket and power it on;
2. Press and hold the switch button for about 10 seconds, the device's indicator light will flash rapidly, indicating it has entered the network pairing mode;
3. Add the device to the network through a gateway device.

Product Dimension Diagram (mm)

