### **Product Introduction**

This 24V thermostat is designed for four-pipe fan coil units, offering precise on/off and fan speed control to maintain the user-set temperature with its built-in sensor. Through Zigbee connectivity, it connects with smart home gateways for remote control and status checking, delivering a seamless and comfortable temperature management experience.

#### **Features**

- Ultra-thin embedded panel
- LED LCD display with touch controls
- Four-pipe fan coil control
- Accurate temperature regulation (±0.5°C)
- 24V low voltage power supply
- Power-loss protection, saving all user settings




- Product Model: BAC-006AZB
- Input Power: 24V DC/AC 50/60Hz
- Fan Speed Relay Rated Current: 5A
  (Resistive) / 3A (Inductive)
- Valve Relay Rated Current: 3A (Resistive) /
  1A (Inductive)
- Temperature Control Accuracy: ±0.5°C
- Temperature Control Range: 5 ~ 35°C

## Wiring Diagram





- Own Power Consumption: ≤1.5W
- Communication Method: Zigbee
- Temperature Sensing Element: NTC3950, 10K
- Shell Material: PC+ABS (Flame Retardant)
- Dimensions: 86×86×41.8mm
- Operating Temperature: 0 ~ 45°C
- Operating Humidity: 5 ~ 95%RH
  (Non-condensing)





# Networking method

- 1. Ensure proper wiring and power up the device.
- 2. Tap \( \text{ to enter screen-off mode.} \)
- 3. Press and hold the  $\checkmark$  button for 10 seconds until the  $\stackrel{\frown}{\circ}$  icon appears and flashes, indicating the device has entered pairing mode.
- 4. Add to the network through the gateway device.

# Product Dimension Diagram (mm)

