


# Alcatel

## Temporis IP100



### IP technology serving for simplicity

- 10 speed dial memories for one-touch access to your top contacts
- Dual-color BLF to easily monitor your lines
- Headset support for your convenience in office environments
- User-friendly interface giving access to usual business features
- Two call appearances

-  1 SIP account
-  10 function keys
-  Headset connection
-  Wall mountable

# Temporis IP100



## MAIN FEATURES

- 1 sip account
- Power over Ethernet
- RJ9 headset port and headset key
- Call log: available on web user interface
- Phonebook: available on web user interface

## FUNCTION SUPPORT

- Multiple call operation (up to 2)
- 10 function keys, 5 of them dual color backlit (up to 18 virtual keys)
- 10 speed dial memories (press & hold)
- Alert indicators (incoming call, MWI, mute, headset, no service)
- Mute, hold, transfer, call forward, redial
- Network conference, local 3-way conference
- 10 built-in melodies
- Do Not Disturb
- Call Return
- Volume control (handset, headset and ringers)
- Dial plans
- Anonymous call, ACR

## IP PBX INTEGRATION

- Network conference
- BLF, BLA
- DND&CF sync
- Intercom, paging, music on hold
- Group pickup, call park

## KEY PAD

- Hold, transfer, conference, redial, voicemail
- 10 line/function programmable keys (18 virtual keys)
- Volume up and down, mute and headset keys

## INTERFACES

- 1 RJ-45 auto sensing 10/100Mbps (for LAN)
- 1 RJ-9 port for handset connection
- 1 RJ-9 port for headset connection
- 5Vdc power jack

## TECHNICAL SPECIFICATIONS

- VoIP Protocol Support :
  - SIPv2 (RFC3261)
- Voice Features :
  - G722, G711A, G711u, G726, G729ab
  - VAD, CNG, AEC, PLC, AJB, AGC
- Network Features:
  - DHCP/Static
  - DNS Srv, redundant server support
  - STUN
  - DTMF: In band, RFC2833, SIP Info
  - 802.1x, LLDP
  - QOS 802.1p/Q, DSCP
- Security Features:
  - TLS
  - SRTP
  - HTTPS with mutual certificate authentication
  - Config file AES encryption
  - 2 level access privileges (user/admin)

## CONFIGURATION AND MANAGEMENT

- IP address Assignment :
  - DHCP, Static IP
- Configuration Support :
  - Keypad
  - Web browser management (Admin/User), HTTP/HTTPS
  - Autoprovision with HTTP/HTTPS/TFTP, APRT support
  - Pcap tracing, syslog

## PHYSICAL & ENVIRONMENTAL

- Mounting :
  - Adjustable footstand: 2 positions
  - Wall mountable
- Power over Ethernet :
  - 802.3af, class 2
- Power Adaptor :
  - AC100-240V input, 5Vdc/700mA output (not included, order separately)
- Power consumption:
  - 0.9-1.8W
- Operating temperature :
  - From -5° to 45°C
- Operating Humidity :
  - Up to 95% non-condensing
- Storage temperature :
  - Up to 60°C

## COMMERCIAL REFERENCE

Temporis IP100

3700601409451

Sales & Marketing Department: ATLINKS Europe-147 avenue Paul Doumer- 92500 Rueil Malmaison. ATLINKS Europe is a simplified joint stock company capitalized at €500,000. Registered under no. 508 823 747 in the Nanterre Trade and Business Register. The manufacturer reserves the right to change product features to deliver technical improvements or comply with new regulations. Alcatel is a trademark of Nokia, used under license by ATLINKS. © Copyright ATLINKS 2017. Reproduction prohibited. Non binding pictures.

[www.alcatel-business.com](http://www.alcatel-business.com)

**Partner NET**

SMART ICT DISTRIBUTION

[www.partnernet-ict.com](http://www.partnernet-ict.com) • [sales@partnernet-ict.com](mailto:sales@partnernet-ict.com)