

Alcatel

Temporis IP901G



Top contacts or features at fingertips

- A user-friendly and highly customizable desk phone which easily becomes your office tool thanks to its **large color touch screen**
- Pair a cordless handset and/or headset on the **embedded DECT base and benefit from mobility**
- In the web 2.0 era, paper memory labels are over. Temporis IP901G offers **30 paperless self-labelled multifunction keys**
- Make sure your meeting minutes are comprehensive thanks to the **call recording** feature.



Embedded DECT base



5" color touch screen



30 self-labelled keys



2 Gigabit Ethernet ports

Temporis IP901G



MAIN FEATURES

- 5", 480x800 pixel, TFT, 24bit color touch screen
- 8 sip accounts
- Power over Ethernet, 2 Gigabit Ethernet ports
- Full duplex hands free
- Supports one Alcatel IP15 accessory cordless handset and one Alcatel IP70H accessory cordless headset (not included)
- Wideband audio
- 2.5mm corded headset port; headset key
- Call log: 200 entries (received, dialed, missed), accessible for IP15 HS
- Phonebook: local (1000 entries, downloadable), LDAP, black list, click-to-dial accessible for IP15 handset
- Micro SD card slot for local call recording
- Built-in languages: 10, 1 downloadable
- SUOTA firmware upgrade for IP15 handsets

FUNCTION SUPPORT

- Multiple call operation (up to 10)
- 30 paperless self-labelled programmable line/function keys
- Alert indicators (incoming call, MWI, no service, headset, mute, DND activated)
- Mute, hold, transfer, call forward, call deflection, redial, 3-way conference
- 10 built-in melodies, .wav downloadable ringtone
- Do Not Disturb
- Auto answer, call return
- Intercom, multicast paging
- Volume control (handset, speakerphone, headset and ringers)
- Dial plans, anonymous call, ACR, hot line, prefix replacement forbidden numbers
- Local call recording (micro SD card requested, not provided)
- XML browser, action urls, uri commands
- Keypad lock (3 levels)
- Handset locator

IP PBX INTEGRATION

- Network conference
- BLF, BLA, DND&CF sync
- Intercom, zone paging, music on hold (local tone or remote)
- Group pickup, call park, call completion
- Configurable progress tones, distinctive ringing

KEY PAD

- OK, cancel, hold, redial
- 4-way navigation key
- Volume up and down, mute, hands free and headset keys

COMMERCIAL REFERENCE

Temporis IP901G

3700601415551

Sales & Marketing Department: ATLINKS Europe-147 Avenue Paul Doumer-92500 Rueil-Malmaison-France. ATLINKS Europe is a simplified joint stock company capitalized at €500,000. Registered under no. 508 823 747 in the Nanterre Trade and Business Register. The manufacturer reserves the right to change product features to deliver technical improvements or comply with new regulations. Alcatel is a trademark of Nokia, used under license by ATLINKS. © Copyright ATLINKS 2017. Reproduction prohibited. Photos are non-contractual

TECHNICAL SPECIFICATIONS

- VoIP Protocol Support:
 - SIPv2 (RFC3261)
- Voice Features:
 - G722, G711A, G711u, G726, G729ab, iLBC
 - VAD, CNG, AEC, PLC, AJB, AGC
 - Full duplex speakerphone
- Network Features:
 - DHCP/Static/PPPoE
 - IPv4/IPv6
 - DNS Srv, redundant server support
 - STUN
 - DTMF: in band, RFC2833, SIP Info
 - 802.1x, LLDP, port mirroring
 - QoS 802.1p/Q, DSCP
- Security Features:
 - TLS
 - SRTP
 - HTTPS with mutual certificate authentication
 - Server and client certificate upload
 - Config file AES encryption
 - 2 level access privileges (user/admin)
 - Password dial masking

CONFIGURATION & MANAGEMENT

- IP address Assignment:
 - DHCP, static IP, PPPoE
- Configuration Support:
 - Keypad
 - Web browser management (Admin/User), HTTP/HTTPS
 - Autoprovision with PnP, HTTP/HTTPS/TFTP/FTP, APRT support
 - SUOTA wireless firmware upgrade for IP15 DECT handset
 - One click config generation
 - TR069
 - Pcap tracing, syslog

PHYSICAL & ENVIRONMENTAL

- Mounting:
 - Multiposition adjustable foot stand: 2
 - Wall mountable
- Power over Ethernet:
 - 802.3af
- Power Adaptor:
 - AC100-240V input, 5Vdc/1500mA output (not included, order separately)
- Operating temperature:
 - From -5 to 45°C
- Operating humidity:
 - Up to 95% non-condensing
- Storage temperature:
 - Up to 60°C

INTERFACES

- Embedded DECT base: 1880MHz-1900MHz
- 2 RJ-45 auto sensing 10/100/1000Mps (LAN/PC)
- 1 RJ-9 port for handset connection, 1 jack (2,5mm) for headset connection
- 1 micro SD card slot
- 5Vdc power jack

www.alcatel-business.com

Partner NET

SMART ICT DISTRIBUTION

www.partnernet-ict.com • sales@partnernet-ict.com