



RG-EW1200 1200Mbps Dual-band Gigabit Wireless Router

DATASHEET



Highlights


- Support 802.11ac wave2
- 4 Omnidirectional antennas provide strong Wi-Fi signal
- Concurrently support up to 96 devices connection
- Reyee Mesh builds up flexible multi-solutions for your network
- Easy network management at your fingertips with Reyee Router App

Highlight Features









Highlight Features



Good Helper for Your Family Management

Parental Control

Health Mode

Ruijie Cloud App allows you to manage the internet access authority of the specified terminal, including the time limit, URL blocking and black/white list setup.

Parental Control

Health Mode


The health mode limits the radiation exposure and blacks out the indicator lights for you to have a good sleep.



Concurrently Support Multiple Devices Connection

Dual-Band integration together with the MU-MIMO technology offer low interference and fast speed internet to up to 96 terminals simultaneously









	Basic
Dimensions (W×D×H)	182 mm x 120 mm x 32 mm (7.17 in. × 4.72 in. × 1.26 in. antennas not included)
Weight	0.22 kg (packages not included)
Wi-Fi Standards	Wi-Fi 5 (802.11ac)
MIMO	2.4 GHz, 2×2, MU-MIMO 5 GHz, 2×2, MU-MIMO
Max. Wi-Fi Speed	2.4 GHz: 300 Mbps 5 GHz: 867 Mbps
Channel Width	2.4 GHz: Auto/20/40 MHz 5 GHz: Auto/20/40/80 MHz
Antennas	4
Antennas Type	External Omnidirectional
Antenna Gain	2.4 GHz: 5 dBi 5 GHz: 5 dBi
WAN Port	1×10/100 Base-T Port
LAN Ports	3×10/100 Base-T Ports
Recommended Users	24
Max. Users	96
Power Supply	DC 12V/0.6A
Power Consumption	≤8.2W
Operation Frequency Bands	802.11b/g/n: 2.400 GHz to 2.483 GHz 802.11a/n/ac: 5.150 GHz to 5.350 GHz 802.11a/n/ac: 5.470 GHz to 5.725 GHz , 5.725 GHz to 5.850 GHz country-specific restrictions apply
Transmit Power	Regular: CE EIRP: ≤20 dBm (2.4 GHz) ≤27 dBm (5 GHz)
Operating Temperature	0 °C to +45 °C (32 °F to 113 °F)
Operating Humidity	5% to 95% Noncondensing
Certifications	CE, RoHS





Wireless		
OFDMA	-	
MU-MIMO	~	
BSS Coloring	-	
Maximum Number of SSIDs	6	
SSID Hiding	✓	
Band Steering	✓	
Guest Wi-Fi	✓	
WPA/WPA2	✓	
WPA3	-	
Roaming	Layer 2 Roaming	
Blacklist	✓	
Reyee Mesh	✓	
Mesh Pairing by Hardware	✓	
Mesh Pairing by Mesh Button	✓	
Mesh Pairing by Eweb	✓	
Recommended Hop Count	≤5	
Wi-Fi Optimization	✓	
QoS (WMM)	✓	
WPS	-	
Transmission Power Adjustment	~	
Hardware Control of the Control of t		
CPU	MT7628	
Flash	16M	

Specifications



	Hardware	
RAM/SDRAM	64M	
Color	White	
System LED Indicator	✓	
Reyee Mesh LED Indicator	-	
Reyee Mesh Button	✓	
Power Button	-	
Reset Button	✓	
DC Connector Dimensions	5.5 mm x 2.1 mm x 10 mm (0.22 in. × 0.08 in. × 0.39 in. antennas not included)	
	WAN	
Static IP	✓	
DHCP	✓	
PPPoE	✓	
Learning PPPoE Account & Password	✓	
VLAN Tagging	✓	
	LAN	
DHCP Server	✓	
Client List	✓	
Static IP Assignment	✓	
Port-Based Flow Control	✓	
Features		
IPv6	✓	
DDNS	✓	
IPTV	✓	

Specifications



Features Features	
Alarm	~
Diagnosis	✓
UPnP	~
ARP Binding	✓
Port Mapping	~
DMZ Host	✓
Rate Limitation of Terminals	✓
Hardware Acceleration	✓
MAC Address Cloning	~
Cloud Management	✓
Repeater Mode	~
WISP Mode	-
	Security
PPTP VPN Server	-
PPTP VPN Client	✓
L2TP VPN Client	-
Parental Control	✓
Protect TCP Flood Attacks	✓
Protect ICMP Attacks	✓
Protect UDP Flood Attacks	✓
System Sy	
Default Access/Password	192.168.110.1 No Password Required by Default
URL Access	✓

Specifications



System	
Local Upgrade	✓
Online Upgrade	✓
APP Upgrade	✓
Syslog	-
Backup	✓
Factory Reset	✓
Language	Chinese English Vietnamese Indonesian Thai Arabic Traditional Chinese Spanish Russian

Package Contents

Model	RG-EW1200
Wireless Router	1
Power Adapter	1
Quick Start Guide	1
Cat5e UTP Cable	1



Redefine your easy network









sales@partnernet-ict.com | +30 210 710 0000 | www.partnernet-ict.com